

Obsolete



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

**1N957B
THRU
1N982B**

Features

- Zener Voltage 6.8V to 75
- Silicon Planar Power Zener Diodes
- V_Z - tolerance $\pm 5\%$
- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)
- Moisture Sensitivity Level 1

Mechanical Data

- Case: DO-35 glass case
- Marking : Cathode band and type number
- Weight: Approx. 0.13 gram

Maximum Ratings

	Symbol	Value	Units
Zener Current		See Table 1	
Power Dissipation @ $T_A=25^\circ\text{C}$ (Note2)	P_{tot}	500	mW
Junction Temperature	T_J	200	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-65 to 200	$^\circ\text{C}$


Electrical Characteristics @ 25°C Unless Otherwise Specified

	Symbol	Maximum	Unit
Thermal resistance	$R_{\theta JA}$	300	$^\circ\text{C/W}$
Forward Voltage @ $I_F=200\text{mA}$	V_F	1.5	V

NOTE: 1. Lead in Glass Exemption Applied, see EU Directive Annex 7(C)-I.
2. Valid provided that a distance of 8mm from case are kept at ambient temperature

**0.5W Silicon Planar
Zener Diodes**

DO-35



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	---	.166	---	4.2	
B	---	.079	---	2.00	
C	---	.020	---	.52	
D	1.000	---	25.40	---	

1N957B thru 1N982B

MCC PART NUMBER	ZENER VOLTAGE ³⁾ @TEST CURRENT		MAXIMUM ZENER IMPEDANCE ¹⁾		MAXIMUM REVERSE LEAKAGE CURRENT TEST-VOLTAGE		MAXIMUM ZENER CURRENT	
	V _Z	I _{ZT}	Z _{ZT}	Z _{ZK}	I _{ZK}	I _R ²⁾	V _R	I _{ZM} ²⁾
	V	mA	Ω	Ω	mA	μA	V	mA
1N957B	6.8	18.5	4.5	700	1.0	150	5.2	47
1N958B	7.5	16.5	5.5	700	0.5	75	5.7	42
1N959B	8.2	15	5.5	700	0.5	50	6.2	38
1N960B	9.1	14	5.5	700	0.5	10	6.9	35
1N961B	10	12.5	5.5	700	0.25	5	7.6	32
1N962B	11	11.5	5	700	0.25	5	8.4	28
1N963B	12	10.5	11.5	700	0.25	5	9.1	26
1N964B	13	9.5	13	700	0.25	5	9.9	24
1N965B	15	8.5	16	700	0.25	5	11.4	21
1N966B	16	7.8	17	700	0.25	5	12.2	19
1N967B	18	7.0	21	750	0.25	5	13.7	17
1N968B	20	6.2	25	750	0.25	5	15.2	15
1N969B	22	5.6	29	750	0.25	5	16.7	14
1N970B	24	5.2	33	750	0.25	5	18.2	13
1N971B	27	4.6	41	750	0.25	5	20.6	11
1N972B	30	4.2	49	1000	0.25	5	22.8	10
1N973B	33	3.8	58	1000	0.25	5	25.1	9.0
1N974B	36	3.4	70	1000	0.25	5	27.4	8.5
1N975B	39	3.2	80	1000	0.25	5	29.7	7.8
1N978B	51	2.5	125	1500	0.25	5	38.8	5.9
1N979B	56	2.2	150	2000	0.25	5	42.6	5.4
1N982B	75	1.7	270	2000	0.25	5	56	4.1

Note:

- 1) The Zener impedance is derived from the 1kHz AC voltage which results when an AC current having an RMS value equal to 10% of the Zener current (I_{ZT}) is superimposed on I_{ZT}. Zener impedance is measured at two points to insure a sharp knee on the breakdown curve and to eliminate unstable units.
- 2) Valid provided that leads are kept at ambient temperature at a distance of 8mm from case.
- 3) Measured with device junction in thermal equilibrium.



TM

Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 10Kpcs/Reel
Part Number-AP	Ammo Packing: 5Kpcs/Ammo Box
Part Number-BP	Bulk: 100Kpcs/Carton

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com