


1-Line Bi-directional Ultra Low Capacitance ESD

Features

- Transient protection:
 - IEC 61000-4-2 (ESD) $\pm 15\text{kV}$ (Air), $\pm 15\text{kV}$ (Contact)
 - IEC 61000-4-5 (Lightning) 5A (8/20 μs)
- Bi-directional ESD protection of single line
- Reverse working voltage, V_{RWM} : 18V
- Capacitance: 0.5pF (typical)
- Clamping voltage: 8V (max)
- Reverse leakage current: 100nA max at $V_{\text{R}} = 18\text{V}$
- Solid-state silicon-avalanche



CSP0201




Applications

- DisplayPort interface
- MDDI Ports
- USB Ports
- Digital Video Interface

Mechanical Data

- Package: CSP0201
- Moisture Sensitivity Level 1, per J-STD-020
- Halogen Free. "Green" Device ^(Note1)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Body Marking and Pin Layout

Marking Code	Simplified Outline	Internal Structure
	 Transparent top view	

Ordering Information

Product Name	Reel Size	Packing Type	Qty/Reel
CSPSBULC18VAE-TP	7"	Tape & Reel	10,000

For packaging details, visit our website at <https://www.mccsemi.com/Package/List>

1-Line Bi-directional Ultra Low Capacitance ESD

Maximum Ratings (T_A=25°C unless otherwise specified)


Parameter	Symbol	Rating	Unit
IEC61000-4-2(ESD)	Air	V _{ESD}	±15
	Contact	V _{ESD}	±15
Peak Pulse Current (8/20μs) (Note 2)	I _{PP}	5	A
Peak Pulse Power (8/20μs) (Note 2)	P _{PK}	35	W
Operating Temperature Range	T _J	-55 to +125	°C
Storage Temperature Range	T _{STG}	-55 to +150	°C

Note:

- Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and 1000ppm antimony compounds.
- Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC61000-4-5.

Parameter Definition

Symbol	Parameter
V _{RWM}	Peak Reverse Working Voltage
I _R	Reverse Leakage Current @ V _{RWM}
V _{BR}	Breakdown Voltage @ I _T
I _T	Test Current
I _{PP}	Maximum Reverse Peak Pulse Current
V _C	Clamping Voltage @ I _{PP}
V _{TRIG}	Reverse Trigger Voltage
I _{TRIG}	Reverse Trigger Current
V _{HOLD}	Reverse Holding Voltage
I _{HOLD}	Reverse Holding Current
C _J	Junction Capacitance
P _{PK}	Peak Pulse Power



Electrical Characteristics (T_A=25°C unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Working Voltage	V _{RWM}				18	V
Reverse Breakdown Voltage	V _{BR}	I _T = 1mA	19	22	25	V
Reverse Leakage Current	I _R	V _{RWM} = 18V			0.1	μA
Clamping Voltage (Note3)	V _C	I _{PP} = 1A, t _p = 8/20μs		4	5	V
		I _{PP} = 5A, t _p = 8/20μs		6	8	
Clamping Voltage (Note4)	V _C	I _{PP} = 4A(TLP)		5		V
		I _{PP} = 16A(TLP)		8		
ESD Trigger Voltage	V _{TRIG}	t _p = 100ns, T _A = 25°C		23		V
Reverse Holding Voltage	V _{HOLD}			2.9		V
Junction Capacitance	C _J	V _R = 0V, f = 1MHz		0.5	0.8	pF
Dynamic Resistance (Note4)	R _{DYN}	TLP, t _p = 100ns		0.26		Ω

Note:

- Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC61000-4-5.
- TLP parameter: Z₀ = 50Ω, t_p = 100ns, t_r = 2ns, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.

1-Line Bi-directional Ultra Low Capacitance ESD

Curve Characteristics

Fig. 1 - 8 X 20 μ s Pulse Waveform




Fig. 2 - Pulse Derating Curve




Fig. 3 - Capacitance Characteristics




Fig. 4 - Clamping Voltage Characteristics




Fig. 5 - TLP Curve





Fig. 6 - Insertion Loss VS.Frequency



1-Line Bi-directional Ultra Low Capacitance ESD

Fig. 7- Return Loss VS.Frequency






Fig. 8 - Eye Diagram (10 Gbps)




Package Outline



DIM	INCH		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.009	0.013	0.23	0.34	
A1	0.000	0.002	0.00	0.05	
b	0.008	0.011	0.21	0.28	
D	0.022	0.026	0.55	0.65	
E	0.010	0.014	0.25	0.35	
e	0.014		0.36		TYP
L	0.006	0.009	0.16	0.22	

Suggested Pad Layout (Unit:mm)



Notes:

1. The suggested land pattern dimensions have been provided for reference only.
2. For further information, please refer to document IPC-7351A.

DISCLAIMERS

Micro Commercial Components Corp. (MCC) reserves the right to make changes to any product without prior notice, including corrections, modifications, enhancements, improvements, or other changes. MCC's products are not designed, authorized, or warranted for use in medical, military, aircraft, space, or life support equipment, nor in applications where failure or malfunction of an MCC product can reasonably be expected to result in personal injury, death, or severe property or environmental damage. MCC does not assume liability for any application or use of the products described herein, nor does it convey any license under its patent rights or those of others. Users of MCC's products in any such application assume all risks associated with their use and agree to hold MCC and all companies whose products are represented on our website harmless against any damages. MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of MCC.

Counterfeiting of semiconductor parts is an increasing problem in the industry. MCC is taking strong measures to protect both ourselves and our customers from counterfeit products. We strongly encourage customers to purchase our parts either directly from MCC or through Authorized Distributors, who are listed by country on our website. Products purchased directly from MCC or from Authorized Distributors are genuine, have full traceability, and meet our quality standards for handling and storage. MCC will not provide warranty coverage or any other assistance for parts bought from Unauthorized Sources.

This document, along with the item(s) described within, may be subject to export control regulations. Exporting these items may require prior authorization from national authorities.

Terms and Conditions - MCC products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.