

Features

- High Breakdown Voltage to 1200V for Improved Reliability
- Maximum Junction Temperature 175°C
- Including fast & soft recovery anti-parallel FWD
- Positive Temperature Coefficient
- Halogen Free. "Green" Device (Note 1)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant (Note 2)("P" Suffix Designates RoHS Compliant. See Ordering Information)

Applications

- Resonant converters
- Uninterruptible power supplies
- Mid to high range switching frequency



Maximum Ratings

Parameter	Symbol	Rating	Unit
Collector-Emitter Voltage	V_{CE}	1200	V
DC Collector Current ⁽³⁾	$T_C=25^\circ\text{C}$	150	A
	$T_C=100^\circ\text{C}$	75	
Pulsed Collector Current ⁽⁴⁾ , $V_{GE}=15\text{V}$	$I_{C,pluse}$	300	A
Diode Forward Current ⁽³⁾	$T_C=25^\circ\text{C}$	150	A
	$T_C=100^\circ\text{C}$	75	
Diode Pulsed Current ⁽⁴⁾	$I_{F,pluse}$	300	A
Continuous Gate-Emitter Voltage	V_{GE}	± 20	V
Transient Gate-Emitter Voltage ⁽⁵⁾		± 30	
Turn off Safe Operation Area $V_{CE} \leq 1200\text{V}$, $T_j \leq 150^\circ\text{C}$		300	A
Power Dissipation	$T_C=25^\circ\text{C}$	645	W
	$T_j=175^\circ\text{C}$		

Note:

1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
2. High Temperature Solder Exemptions Applied, see EU Directive Annex 7a.
3. Limited by T_{Jmax} .
4. t_p limited by T_{Jmax} .
5. $t_p \leq 10\mu\text{s}$, Duty Cycle < 1%


Internal Structure



Device Code: MIWP75N120AT1Y
Date Code: YYWW (Year & Week)

Trench and Field Stop IGBT 1200V 75A

TO-247Plus



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.192	0.201	4.90	5.10	
A1	0.090	0.099	2.31	2.51	
A2	0.074	0.083	1.90	2.10	
b	0.044	0.050	1.14	1.26	
b1	0.073	0.085	1.86	2.16	
b2	0.077	0.081	1.96	2.06	
c	0.022	0.026	0.58	0.64	
D	0.822	0.831	20.90	21.10	
D1	0.639	0.664	16.25	16.85	
D2	0.041	0.054	1.05	1.35	
D3	0.022	0.031	0.58	0.78	
E	0.618	0.626	15.70	15.90	
E1	0.515	0.532	13.10	13.50	
E2	0.053	0.061	1.35	1.55	
e	0.214(BSC)		5.44(BSC)		
L	0.778	0.791	19.78	20.08	
L1	0.158	0.167	4.03	4.23	
R	0.074	0.083	1.90	2.10	

Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
IGBT Static Characteristics						
Collector-Emitter Breakdown Voltage	$V_{(BR)CES}$	$V_{GE}=0V, I_C=250\mu A$	1200			V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=75A, T_J=25^\circ C$		1.55	1.9	V
		$V_{GE}=15V, I_C=75A, T_J=125^\circ C$		1.8		
		$V_{GE}=15V, I_C=75A, T_J=150^\circ C$		1.9		
G-E Threshold Voltage	$V_{GE(th)}$	$I_C=2.6mA, V_{CE}=V_{GE}$	4.8	5.6	6.4	V
C-E Leakage Current	I_{CES}	$V_{CE}=1200V, V_{GE}=0V, T_J=25^\circ C$			0.25	mA
		$V_{CE}=1200V, V_{GE}=0V, T_J=150^\circ C$			5	
G-E Leakage Current	I_{GES}	$V_{CE}=0V, V_{GE}=\pm 20V$			± 100	nA
Dynamic Characteristics						
Input Capacitance	C_{ies}	$V_{CE}=25V, V_{GE}=0V, f=1MHz$		6.92		nF
Reverse Transfer Capacitance	C_{res}			0.06		
Gate Charge	Q_G	$V_{CC}=600V, I_C=75A, V_{GE}=15V$		0.48		μC
Short Circuit Collector Current	I_{SC}	$V_{GE}=15V, t_{SC}\leq 10\mu s, V_{CC}=600V$		350		A
IGBT Switching Characteristics						
Turn-On Delay Time	$t_{d(on)}$	$V_{CC}=600V, I_C=75A, V_{GE}=-5V\sim 15V, R_G=10\Omega, T_J=25^\circ C$		135		ns
Rise Time	t_r			106		
Turn-Off Delay Time	$t_{d(off)}$			345		
Fall Time	t_f			210		
Turn-On Energy	E_{on}			8.5		mJ
Turn-Off Energy	E_{off}			5.1		
Turn-On Delay Time	$t_{d(on)}$	$V_{CC}=600V, I_C=75A, V_{GE}=-5V\sim 15V, R_G=10\Omega, T_J=125^\circ C$		135		ns
Rise Time	t_r			110		
Turn-Off Delay Time	$t_{d(off)}$			365		
Fall Time	t_f			315		
Turn-On Energy	E_{on}			10.5		mJ
Turn-Off Energy	E_{off}			7.0		
Turn-On Delay Time	$t_{d(on)}$	$V_{CC}=600V, I_C=75A, V_{GE}=-5V\sim 15V, R_G=10\Omega, T_J=150^\circ C$		135		ns
Rise Time	t_r			121		
Turn-Off Delay Time	$t_{d(off)}$			375		
Fall Time	t_f			345		
Turn-On Energy	E_{on}			10.8		mJ
Turn-Off Energy	E_{off}			7.5		





Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Diode Characteristics						
Diode Forward Voltage	V_F	$V_{GE}=0V, I_F=75A, T_j=25^{\circ}C$		2.0	2.6	V
		$V_{GE}=0V, I_F=75A, T_j=125^{\circ}C$		1.9		
		$V_{GE}=0V, I_F=75A, T_j=150^{\circ}C$		1.8		
Reverse Recovery Current	I_{rr}	$V_R=600V, I_F=75A,$ $di_F/dt=-500A/\mu s, T_j=25^{\circ}C$		9		A
Diode Reverse Recovery Time	t_{rr}			268		ns
Reverse Recovery Charge	Q_{rr}			3.42		μC
Reverse Recovery Energy	E_{rec}			1.52		mJ
Reverse Recovery Current	I_{rr}	$V_R=600V, I_F=75A,$ $di_F/dt=-500A/\mu s, T_j=125^{\circ}C$		12		A
Diode Reverse Recovery Time	t_{rr}			337		ns
Reverse Recovery Charge	Q_{rr}			6.58		μC
Reverse Recovery Energy	E_{rec}			3.18		mJ
Reverse Recovery Current	I_{rr}	$V_R=600V, I_F=75A,$ $di_F/dt=-500A/\mu s, T_j=150^{\circ}C$		14		A
Diode Reverse Recovery Time	t_{rr}			375		ns
Reverse Recovery Charge	Q_{rr}			9.45		μC
Reverse Recovery Energy	E_{rec}			3.73		mJ





Thermal characteristics

Parameter	Symbol	Min	Typ	Max	Units
Operating Junction Temperature Range	T_J	-40		175	$^{\circ}C$
Storage Temperature Range	T_{stg}	-55		150	$^{\circ}C$
Thermal Resistance from Junction to Case (IGBT)	$R_{th_{J-C}}$		0.23		$^{\circ}C/W$
Thermal Resistance from Junction to Case (Diode)	$R_{th_{J-C}}$		0.35		$^{\circ}C/W$
Thermal Resistance from Junction to Ambient	$R_{th_{J-A}}$			40	$^{\circ}C/W$





Curve Characteristics







Curve Characteristics



Curve Characteristics



Curve Characteristics



Ordering Information

Device	Packing
Part Number-BP	Tube: 30pcs/Tube, 1800pcs/Ctn

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp** . and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.