

### **Features**

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix Designates Compliant. See Ordering Information)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- High Surge Forward Current Capability
- Low Power Losses and High Efficiency
- Halogen Free. "Green" Device (Note 2)

# 3 Amp Low VF Schottky Rectifier 40 to 100 Volts

# **Maximum Ratings**

- Operating Junction Temperature Range:-55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Maximum Thermal Resistance: 17°C/W Junction to Lead

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
SL34B	SL34B	40V	28V	40V
SL36B	SL36B	60V	42V	60V
SL310B	SL310B	100V	70V	100V


# Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I <sub>F(AV)</sub>	3.0A	T <sub>L</sub> =120°C
Peak Forward Surge Current	I <sub>FSM</sub>	60A	8.3ms,Half Sine
Maximum Instantaneous Forward Voltage SL34B SL36B SL310B	V <sub>F</sub>	0.45V 0.5V 0.6V	I <sub>FM</sub> =3.0A; T <sub>J</sub> =25°C
Maximum DC Reverse Current at Rated DC Blocking Voltage	I <sub>R</sub>	0.1mA 10mA	T <sub>J</sub> =25°C T <sub>J</sub> =100°C

#### Note:


- 1. High Temperature Solder Exemptions Applied, See EU Directive Annex 7a.
- 2. Halogen free "Green" products are defined as those which contain < 900 ppm bromine,
- <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

# SMB (DO-214AA)



DIMENSIONS							
DIM	INCHES		MM		NOTE		
DIIVI	MIN	MAX	MIN	MAX	NOTE		
Α	0.079	0.103	2.00	2.62			
В	0.075	0.087	1.91	2.21			
С	0.002	0.008	0.05	0.20			
D	0.006	0.012	0.15	0.31			
Е	0.030	0.060	0.76	1.52			
F	0.065	0.091	1.65	2.32			
G	0.200	0.220	5.08	5.59			
Н	0.160	0.191	4.06	4.85			
J	0.130	0.155	3.30	3.94			

#### Suggested Solder Pad Layout



100



## **Curve Characteristics**




Fig. 3 - Typical Instantaneous Forward Characteristics





Fig. 5 - Typical Instantaneous Forward Characteristics



Current

Current

Current

Peak Forward Surge Current (A)

20

10

0

Fig. 2 - Maximum Non-Repetitive Peak Forward Surge

Fig. 4 - Typical Instantaneous Forward Characteristics

Number of Cycles at 60 Hz

8.3 ms Single Half Sine-Wave





Fig. 6 - Typical Reverse Leakage Characteristics





# **Curve Characteristics**

Fig. 7 - Typical Reverse Leakage Characteristics





Fig. 8 - Typical Reverse Leakage Characteristics





# **Ordering Information**

Device	Packing	
Part Number-TP	Tape&Reel: 3Kpcs/Reel	

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp**. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp**, and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp**, products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Rev.3-3-12012020 4/4 MCCSEMI.COM