











130 W Cochran St, Unit B  
Simi Valley, CA 93065  
Tel:818-701-4933

## Process Change Notification (PCN)

<b>Notification number:</b>	<b>040924-1</b>
<b>Notification date:</b>	<b>09 Apr 2024</b>
<b>Proposed implementation date:</b>	<b>09 Jul 2024</b> (90 days notification before change, according to JEDEC standard)
<b>Product type affected:</b>	Please refer to table 1 in Appendix 1.
<b>Change Category</b>	Additional new 2 <sup>nd</sup> source
<b>Change Classification</b>	Major
<b>Change description:</b>	To solve our delivery issue of RB551V-40-TP&MMBD2004S-TP &DDTA123YCA-TP&DDTC113ZCA-TP&DDTC123YCA-TP, MCC has determined to add a new 2 <sup>nd</sup> source for this one part. Full electrical characterization and high reliability testing has been completed to ensure there is no change to device functionality or electrical specifications in the datasheet.
<b>Reason for change:</b>	Additional new 2nd source to assure continuity of supply.
<b>Deposition of old product</b>	NA
<b>Identification of Changed product:</b>	Identify the change based on Lot NO & DC
<b>Contact person:</b>	Please contact your respective Account manager (AM) / Inside sales representative (ISR/CSR) if you have further query.
<b>Approved by:</b>	Jason Gao (Director of Engineering) Steve Zhang (Director of Supply Chain) Seaman Wu (Director of Quality) Pamela Cheng (General Manager)

Appendix 1: Table 1

No.	Product type	Existing marking	New marking	Package type/code
1	RB551V-40-TP	D4	D4	SOD-323
2	MMBD2004S-TP	B6D	B6D	SOT-23
3	DDTA123YCA-TP	234	234	SOT-23
4	DDTC113ZCA-TP	E21A	E21A	SOT-23
5	DDTC123YCA-TP	134	134	SOT-23

Product type	Original source layout	New source layout
RB551V-40-TP		
MMBD2004S-TP		
DDTA123YCA-TP		
DDTC113ZCA-TP		



130 W Cochran St, Unit B  
Simi Valley, CA 93065  
Tel:818-701-4933

---

Date: 09 Apr 2024

PCN #: 040924-1

PCN Title: Additional 2<sup>nd</sup> source for RB551V-40-TP&MMBD2004S-TP&DDTA123YCA-TP&DDTC113ZCA-TP&DDTC123YCA-TP

Dear Customer.

This is a PCN announcement to the above-mentioned product which is/are offered by Micro Commercial Components Corp (MCC). We would appreciate your acknowledgement of receipt of this notification within 30 days of the date of this PCN to your local ISR, sales representative. No acknowledgement from you of this PCN constitutes acceptance to the change. Please refer to the attached document for more information (including implementation date / product date code of this change). If you have any questions or concerns related to this PCN, please contact your local sales representative / ISR for support.

Yours sincerely,

MCC PCN Team



130 W Cochran St, Unit B  
Simi Valley, CA 93065  
Tel:818-701-4933

## Reliability Report

**Part Number: MMBD2004S-TP**

**Date: 2024-03-12**

**Test Results : PASS**

Test Item	Conditions	Duration	Quantity	Rejects
<b>TEST</b> Pre- and Post-Stress Electrical Test	T <sub>a</sub> = 25 °C	N/A	all parts	see below
* <b>Pre-conditioning for MSL 1</b>	JESD22A-113 1. Temperature Cycling:-40 °C ~ 60 °C , 2. Bake:125 °C , 3. Moisture Soak:85 °C , 8 5%RH for MSL1; 4. Reflow*3Cycles:260 °C	5Cycles; 24 hours; 192hours 3Cycles	308Pcs	0
<b>HTRB</b> High Temperature Reverse Bias	MIL-STD-750 Method 1038 T <sub>j</sub> = T <sub>jmax</sub> , 100% VR	1000 hours	77Pcs	0
<b>TC</b> Temperature Cycling	JESD22-A104 -55 °C (+0,-10)/15Min~ 150(+15,-0)/15Min,	1000Cycles (500hours)	77Pcs	0
<b>AC</b> Autoclave	JESD22-A102 T <sub>a</sub> = 121 °C±2 °C , RH = 100 % , 15psig	96 hours	77Pcs	0
<b>H3TRB</b> High Humidity High Temperature Reverse Bias	JESD22-A101 T <sub>a</sub> = 85 °C±2 °C , RH = 85%±5% , 100 % VR (VR MAX=100V)	1000 hours	77Pcs	0
<b>RSH</b> Resistance to Solder Heat	JESD22-B106 260 °C (+5 , -0)	10 s	30Pcs	0
<b>SD</b> Solderability	J-STD-002 235 °C ± 5 °C	3 s	10Pcs	0
<b>HTSL</b> High Temperature Storage Life	JESD22-A103 TstgMax	1000 hours	77Pcs	0

\*Remark : detail MSL of product refer to data sheet on MCC website.



130 W Cochran St, Unit B  
Simi Valley, CA 93065  
Tel:818-701-4933

## Reliability Report

**Part Number: RB551V-40-TP**

**Date: 2024-03-12**

**Test Results : PASS**

Test Item	Conditions	Duration	Quantity	Rejects
<b>TEST</b> Pre- and Post-Stress Electrical Test	T <sub>a</sub> = 25 °C	N/A	all parts	see below
* <b>Pre-conditioning for MSL 1</b>	JESD22A-113 1. Temperature Cycling:-40 °C ~ 60 °C , 2. Bake:125 °C , 3. Moisture Soak:85 °C , 8 5%RH for MSL1; 4. Reflow*3Cycles:260 °C	5Cycles; 24 hours; 192hours 3Cycles	308Pcs	0
<b>HTRB</b> High Temperature Reverse Bias	MIL-STD-750 Method 1038 T <sub>j</sub> = T <sub>jmax</sub> , 100% VR	1000 hours	77Pcs	0
<b>TC</b> Temperature Cycling	JESD22-A104 -55 °C (+0,-10)/15Min~ 125(+15,-0)/15Min,	1000Cycles (500hours)	77Pcs	0
<b>AC</b> Autoclave	JESD22-A102 T <sub>a</sub> = 121 °C±2 °C, RH = 100 % , 15psig	96 hours	77Pcs	0
<b>H3TRB</b> High Humidity High Temperature Reverse Bias	JESD22-A101 T <sub>a</sub> = 85 °C±2 °C , RH = 85%±5%, 100 % VR (VR MAX=100V)	1000 hours	77Pcs	0
<b>RSH</b> Resistance to Solder Heat	JESD22-B106 260 °C (+5 , -0)	10 s	30Pcs	0
<b>SD</b> Solderability	J-STD-002 235 °C ± 5 °C	3 s	10Pcs	0
<b>HTSL</b> High Temperature Storage Life	JESD22-A103 TstgMax	1000 hours	77Pcs	0

\*Remark : detail MSL of product refer to data sheet on MCC website.



130 W Cochran St, Unit B  
Simi Valley, CA 93065  
Tel:818-701-4933

## Reliability Report

**Part Number: DDTA123YCA-TP**

**Date: 2024-04-01**

**Test Results : PASS**

Test Item	Conditions	Duration	Quantity	Rejects
<b>TEST</b> Pre- and Post-Stress Electrical Test	$T_a = 25\text{ }^\circ\text{C}$	N/A	all parts	see below
* <b>Pre-conditioning for MSL 1</b>	JESD22A-113 1. Temperature Cycling: $-40\text{ }^\circ\text{C} \sim 60\text{ }^\circ\text{C}$ , 2. Bake: $125\text{ }^\circ\text{C}$ , 3. Moisture Soak: $85\text{ }^\circ\text{C}$ , 8 5%RH for MSL1; 4. Reflow*3Cycles: $260\text{ }^\circ\text{C}$	5Cycles; 24 hours; 168hours 3Cycles	308Pcs	0
<b>HTRB</b> High Temperature Reverse Bias	MIL-STD-750 Method 1038 $T_j = T_{jmax}$ , 100% Vcbo	1000 hours	77Pcs	0
<b>HAST</b> High Accelerated Temperature and humidity Stress Test	JESD22-A1F€ $125\text{ }^\circ\text{C}$ , 100%RH 80%Vcbo(Max=42V)	96 hours	77Pcs	0
<b>IOL</b> Intermittent Operating Life	MIL-STD-750 Method 1037 $t_{on} = t_{off}$ , devices powered to insure $\Delta T_j = 100\text{ }^\circ\text{C}$ for 15000 cycles	1000 hours	77Pcs	0
<b>ESD</b> <b>Human Body Model</b>	JESD22-A114 2 KV	N/A	30Pcs	0
<b>RSH</b> Resistance to Solder Heat	JESD22-B106 $260\text{ }^\circ\text{C}$ (+5, -0)	10 s	30Pcs	0
<b>SD</b> Solderability	J-STD-002 $235\text{ }^\circ\text{C} \pm 5\text{ }^\circ\text{C}$	3 s	10Pcs	0
<b>HTSL</b> High Temperature Storage Life	JESD22-A103 TstgMax	1000 hours	77Pcs	0

\*Remark : detail MSL of product refer to data sheet on MCC website.