



## Features

- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix Designates Compliant. See Ordering Information)
- Epoxy Meets UL 94 V-0 Flammability Rating
- High Frequency Operation
- High Surge Forward Current Capability
- Planar Structure Die and Soft Recovery Characteristics

## Maximum Ratings @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Value	Unit
Peak Repetitive Reverse Voltage	$V_{RRM}$	1200	V
Working Peak Reverse Voltage	$V_{RWM}$		
DC Blocking Voltage	$V_R$		
RMS Reverse Voltage	$V_{RMS}$	840	V
Average Rectified Forward Current	$I_{F(AV)}$	75	A
Non-Repetitive Peak Surge Current @8.3ms Half Sine Wave	$I_{FSM}$	500	A
Current Squared Time @ 1ms≤t≤8.3ms	$I^2t$	1037	A <sup>2</sup> s


## Internal Structure

Simplified Outline	Graphic Symbol
	

Note :1. High Temperature Solder Exemption Applied, See EU Directive Annex 7a.

# 75 Amp Ultra Fast Recovery Rectifier 1200 Volts

## TO-247AD



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.602	0.642	15.30	16.30	
B	0.799	0.839	20.30	21.30	
C	0.189	0.205	4.80	5.20	
D	0.242		6.15		BSC.
E	0.091	0.106	2.30	2.70	
F	0.768	0.807	19.50	20.50	
G	----	0.189	----	4.80	
H	0.428		10.88		BSC.
I	0.075	0.087	1.91	2.21	
J	0.044	0.054	1.11	1.36	
K	0.189	0.205	4.80	5.20	
O	0.073	0.085	1.85	2.15	
P	0.087	0.103	2.21	2.61	
Q	0.020	0.030	0.51	0.75	
R	0.512	0.535	13.00	13.60	
S	0.640	0.663	16.25	16.85	
T	0.134	0.150	3.40	3.80	Φ
U	----	0.287	----	7.30	Φ

## Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$T_J$	Operating Junction Temperature Range		-55		175	°C
$T_{stg}$	Storage Temperature Range		-55		175	°C
$R_{th(J-C)}$	Thermal Resistance from Junction to Case			0.5		°C/W
$R_{th(J-A)}$	Thermal Resistance from Junction to Ambient	Free in Air		40		°C/W

## Electrical Characteristics @ 25°C Unless Otherwise Specified

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage	$V_F$	$I_F=75A; T_J=25^{\circ}C$		2.30	3.00	V
		$I_F=75A; T_J=125^{\circ}C$		2.00	2.60	
Reverse Current	$I_R$	$V_R=1200V; T_J=25^{\circ}C$			10	$\mu A$
		$V_R=1200V; T_J=125^{\circ}C$			500	
Junction Capacitance	$C_J$	$V_R=4V; f=1MHz; T_J=25^{\circ}C$		250		pF

## Dynamic Recovery Characteristics @ 25°C Unless Otherwise Specified

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> =0.5A; I <sub>R</sub> =1.0A;I <sub>RR</sub> =0.25A;T <sub>J</sub> =25°C			70	90	ns
		I <sub>F</sub> =1A;d <sub>iF</sub> /d <sub>t</sub> =-100A/μs;V <sub>RM</sub> =30V;T <sub>J</sub> =25°C			47		
			T <sub>J</sub> =25°C		254		
			T <sub>J</sub> =125°C		404		
			I <sub>F</sub> =50A d <sub>iF</sub> /d <sub>t</sub> =-500A/μs V <sub>RM</sub> =400V				
		T <sub>J</sub> =25°C		15.8			
Peak Recovery Current	I <sub>RRM</sub>				27.4		
Reverse Recovery Charge	Q <sub>rr</sub>						nC
				T <sub>J</sub> =25°C		1592	
						5308	

## Curve Characteristics

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 - Typical Forward Characteristics




Fig. 4 - Typical Reverse Leakage Characteristics




Fig. 5 - Typical Capacitance Characteristics





Fig. 6 - Reverse Recovery Waveform and Definitions



## Ordering Information

Device	Packing
Part Number-BP	Bulk:30pcs/Tube,360pcs/Box,1.8Kpcs/Carton

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-BP-HF

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.