



E480232

Features

- AEC-Q101 Qualified
- For Surface Mount Applications
- Excellent Clamping Capability
- High Temp Soldering: 260°C / 10 Seconds at Terminals
- Halogen Free. "Green" Device (Note 1)
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant (Note 2) ("P" Suffix Designates RoHS Compliant. See Ordering Information)
- ESD protection of data lines in accordance with IEC 61000-4-2, ±30kV(Air), ±30kV (Contact)

Maximum Ratings

Parameter	Symbol	Value	Unit
Peak Pulse Power Surge Current with a 10/1000µs Waveform (Note 3)	I_{PPM}	See Next Table	A
Peak Pulse Power Dissipation (Note 3)	P_{PPM}	1500	W
Power Dissipation on Infinite Heatsink at $T_L = 75^\circ\text{C}$	P_D	5.0	W
Peak Forward Surge Current Unidirectional Only (Note 4)	I_{FSM}	100	A

Note:

1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
2. High Temperature Solder Exemption Applied, see EU Directive Annex 7a.
3. Non-repetitive current pulse, per Fig.3 and derated above $T_A = 25^\circ\text{C}$ per Fig.4.
4. 8.3ms, single half sine wave duty cycle = 4 pulses per Minutes maximum.


Internal Structure

Description	Simplified outline	Graphic symbol
Uni-directional		
Bi-directional		

XXXX = Marking code YYWW = Date Code

1500 Watt TVS
5.0 to 85
Volts


SMB (DO-214AA)
(LEAD FRAME)



DIMENSIONS

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.079	0.103	2.00	2.62	
B	0.075	0.087	1.91	2.21	
C	0.002	0.008	0.05	0.20	
D	0.006	0.012	0.15	0.31	
E	0.030	0.060	0.76	1.52	
F	0.065	0.091	1.65	2.32	
G	0.200	0.220	5.08	5.59	
H	0.160	0.191	4.06	4.85	
J	0.130	0.155	3.30	3.94	

Suggested Solder Pad Layout



Thermal Characteristics

Parameter	Symbol	Value	Unit
Operating Junction Temperature Range	T_J	-55 to +175	°C
Storage Temperature Range	T_{STG}	-55 to +175	°C
Typical Thermal Resistance Junction to Lead	$R_{\theta JL}$	20	°C/W
Typical Thermal Resistance Junction to Ambient	$R_{\theta JA}$	100	°C/W
Typical Thermal Resistance Junction to Case	$R_{\theta JC}$	15	°C/W

Note:

5. Mounted on 0.2 x 0.2" (5.0 x 5.0 mm) copper pads to each terminal.

Electrical Characteristics @ 25°C Unless Otherwise Specified

MCC Part Number		Reverse Stand-off Voltage	Breakdown Voltage V_{BR} @ I_T		Test Current	Maximum Clamping Voltage @ I_{PP}	Maximum Peak Pulse Current	Maximum Reverse Leakage @ V_R	Marking Code	
Uni	Bi	V_{RWM} (V)	Min (V)	Max (V)	I_T (mA)	V_C (V)	I_{PP} (A)	I_R (μ A)	Uni	Bi
SMB15J5.0AHE3	SMB15J5.0CAHE3	5	6.4	7.07	10	9.2	163	1000	15KE	15AE
SMB15J6.0AHE3	SMB15J6.0CAHE3	6	6.67	7.37	10	10.3	145.6	1000	15KG	15AG
SMB15J6.5AHE3	SMB15J6.5CAHE3	6.5	7.22	7.98	10	11.2	133.9	500	15KK	15AK
SMB15J7.0AHE3	SMB15J7.0CAHE3	7	7.78	8.6	10	12	125	200	15KM	15AM
SMB15J7.5AHE3	SMB15J7.5CAHE3	7.5	8.33	9.21	1	12.9	116.3	100	15KP	15AP
SMB15J8.0AHE3	SMB15J8.0CAHE3	8	8.89	9.83	1	13.6	110.29	50	15KR	15AR
SMB15J8.5AHE3	SMB15J8.5CAHE3	8.5	9.44	10.4	1	14.4	104.17	20	15KT	15AT
SMB15J9.0AHE3	SMB15J9.0CAHE3	9	10	11.1	1	15.4	97.4	10	15KV	15AV
SMB15J10AHE3	SMB15J10CAHE3	10	11.1	12.3	1	17	88.24	5	15KX	15AX
SMB15J11AHE3	SMB15J11CAHE3	11	12.2	13.5	1	18.2	82.42	5	15KZ	15AZ
SMB15J12AHE3	SMB15J12CAHE3	12	13.3	14.7	1	19.9	75.38	5	15LE	15BE
SMB15J13AHE3	SMB15J13CAHE3	13	14.4	15.9	1	21.5	69.77	5	15LG	15BG
SMB15J14AHE3	SMB15J14CAHE3	14	15.6	17.2	1	23.2	64.66	5	15LK	15BK
SMB15J15AHE3	SMB15J15CAHE3	15	16.7	18.5	1	24.4	61.48	5	15LM	15BM
SMB15J16AHE3	SMB15J16CAHE3	16	17.8	19.7	1	26	57.69	5	15LP	15BP
SMB15J17AHE3	SMB15J17CAHE3	17	18.9	20.9	1	27.6	54.35	5	15LR	15BR
SMB15J18AHE3	SMB15J18CAHE3	18	20	22.1	1	29.2	51.37	5	15LT	15BT
SMB15J19AHE3	SMB15J19CAHE3	19	21.1	23.3	1	30.8	48.73	5	15LU	15BU
SMB15J20AHE3	SMB15J20CAHE3	20	22.2	24.5	1	32.4	46.3	5	15LV	15BV
SMB15J22AHE3	SMB15J22CAHE3	22	24.4	26.9	1	35.5	42.25	5	15LX	15BX
SMB15J24AHE3	SMB15J24CAHE3	24	26.7	29.5	1	38.9	38.56	5	15LZ	15BZ
SMB15J26AHE3	SMB15J26CAHE3	26	28.9	31.9	1	42.1	35.63	5	15ME	15CE
SMB15J28AHE3	SMB15J28CAHE3	28	31.1	34.4	1	45.4	33.04	5	15MG	15CG
SMB15J30AHE3	SMB15J30CAHE3	30	33.3	36.8	1	48.4	30.99	5	15MK	15CK
SMB15J33AHE3	SMB15J33CAHE3	33	36.7	40.6	1	53.3	28.14	5	15MM	15CM
SMB15J36AHE3	SMB15J36CAHE3	36	40	44.2	1	58.1	25.82	5	15MP	15CP
SMB15J40AHE3	SMB15J40CAHE3	40	44.4	49.1	1	64.5	23.26	5	15MR	15CR
SMB15J43AHE3	SMB15J43CAHE3	43	47.8	52.8	1	69.4	21.61	5	15MT	15CT
SMB15J45AHE3	SMB15J45CAHE3	45	50	55.3	1	72.7	20.63	5	15MV	15CV
SMB15J48AHE3	SMB15J48CAHE3	48	53.3	58.9	1	77.4	19.38	5	15MX	15CX
SMB15J51AHE3	SMB15J51CAHE3	51	56.7	62.7	1	82.4	18.2	5	15MZ	15CZ
SMB15J54AHE3	SMB15J54CAHE3	54	60	66.3	1	87.1	17.22	5	15NE	15DE
SMB15J58AHE3	SMB15J58CAHE3	58	64.4	71.2	1	93.6	16.03	5	15NG	15DG
SMB15J60AHE3	SMB15J60CAHE3	60	66.7	73.7	1	96.8	15.5	5	15NK	15DK
SMB15J64AHE3	SMB15J64CAHE3	64	71.1	78.6	1	103	14.56	5	15NM	15DM
SMB15J70AHE3	SMB15J70CAHE3	70	77.8	86	1	113	13.27	5	15NP	15DP
SMB15J75AHE3	SMB15J75CAHE3	75	83.3	92.1	1	121	12.4	5	15NR	15DR
SMB15J78AHE3	SMB15J78CAHE3	78	86.7	95.8	1	126	11.9	5	15NT	15DT
SMB15J80AHE3	SMB15J80CAHE3	80	88.8	97.6	1	129.6	11.57	5	15NU	15DU
SMB15J85AHE3	SMB15J85CAHE3	85	94.4	104	1	137	10.95	5	15NV	15DV

Curve Characteristics

Fig.1-Peak Pulse Power Rating Curve




Fig. 2 - Typical Junction Capacitance




Fig. 3 - Pulse Waveform





Fig. 4 - Pulse Derating Curve



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel:3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp.** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** . and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.