

Features

- Solid-state silicon technology
- Protects 4 I/O Lines
- Low Capacitance
- Low Clamping Voltage
- Low leakage current
- Moisture Sensitivity Level 1
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings


IEC61000-4-2(ESD)	Air	±25KV
	Contact	±25KV
Peak Pulse Power (8/20µs)	P _{PK}	54W
Peak Pulse Current (8/20µs) ^(Note 2)	I _{PP}	4.5A
Operating Junction Temperature Range	T _J	-40°C to +125°C
Storage Temperature Range	T _{STG}	-55°C to +150°C

Note:


1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

2. Non-repetitive current pulse 8/20 µs exponential decay waveform according to IEC61000-4-5.

Marking Information




Internal Structure



ESD Protection Device

SOT23-6L



DIMENSIONS

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.012	0.020	0.30	0.50	
B	0.051	0.070	1.30	1.80	
C	0.087	0.126	2.20	3.20	
D	0.037		0.95		TYP.
G	0.074		1.90		TYP.
H	0.106	0.122	2.70	3.10	
J	0.002	0.006	0.05	0.15	
K	0.030	0.051	0.75	1.30	
L	0.012	0.024	0.30	0.60	
M	0.003	0.008	0.08	0.22	

Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
I/O Pins						
Reverse Working Voltage	V_{RWM}				5	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	7		9	V
Reverse Leakage Current	I_R	$V_{RWM}=5V$			100	nA
Forward Voltage	V_F	$I_T = 10mA$	0.6	0.9	1.2	V
Clamping Voltage ^(Note 1)	V_C	$V_{ESD}=8KV$		13		V
Clamping Voltage ^(Note 2)	V_C	$I_{PP}=1A, t_p=8/20\mu s$		7.8	9	V
Clamping Voltage ^(Note 2)	V_C	$I_{PP}=4.5A, t_p=8/20\mu s$		10	12	V
Junction Capacitance	C_J	$V_R=0V, f=1MHz,$ Any I/O pin to GND		0.5	0.7	pF
Junction Capacitance	C_J	$V_R=0V, f=1MHz,$ Between any I/O pins		0.2	0.4	pF
Dynamic Resistance ^(Note 3)	R_{DYN}	$t_p=100ns$		0.31		Ω
VDD Pins						
Reverse Working Voltage	V_{RWM}				5.5	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR}=1mA$	7		8.5	V
Reverse Leakage Current	I_R	$V_{RWM}=5.5V$			100	nA
Forward Voltage	V_F	$I_F = 10mA$	0.6	0.9	1.2	V
Clamping Voltage ^(Note 1)	V_C	$V_{ESD}=8KV$		10		V
Clamping Voltage ^(Note 2)	V_C	$I_{PP}=1A, t_p=8/20\mu s$		7.8	9	V
Clamping Voltage ^(Note 2)	V_C	$I_{PP}=15A, t_p=8/20\mu s$		11.2	13	V
Dynamic Resistance ^(Note 3)	R_{DYN}	$t_p=100ns$		0.20		Ω

Note:

1. Contact Discharge Mode, According to IEC61000-4-2.
2. Non-repetitive Current Pulse, According to IEC61000-4-5.
3. TLP Parameter: $Z_0=50\Omega, t_p=100ns, t_r=2ns$, Averaging Window from 60ns to 80ns. R_{DYN} is Calculated from 4A to 16A.

Curve Characteristics

Fig. 1 - 8 X 20µs Pulse Waveform




Fig. 2 - Non-Repetitive Peak Pulse Power




Fig. 3 - Capacitance Characteristics




Fig. 4 - Clamping Voltage Characteristics




Fig. 5 - TLP Measurement -I/O to GND





Fig. 6 - Pulse Derating Curve



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.